
SPL03.2701.15

Grünzell®

Description

The 5W Mitsu Spot is excellent for both indoor and exterior use. Its durable construction makes it ideal for illuminating architectural elements, garden features and outdoor living spaces. Its attractive design also makes it ideal for indoor feature lighting or as a reading light





1	150° 140°	160° 1	° 170°	180	
130°	$\langle \rangle$	\Box	+		
120°	X	Q	$\stackrel{\text{th}}{\to}$		
110°	H	X	HD)		
100°	14	Æ	UX.		
90°		Ħ	E		
80°	TH	Ŧ	$\langle \nabla \rangle$		
70°	AT	$\langle \mathbf{n} \rangle$	T h		
60°	$\times \!$	X			
500	$\times \land$	X			
50°		4	1	Ý	
	30° 40°	20°) 10°	VA: 01	

LED Lamp	
Luminous Flux	
Colour temperature	
CRI	
MacAdam Ellipse	
Nominal Power	
Beam Angle	
•	

1 415 lm 2700 K 80 3 Step 5W 15°

Ingress Protection
Impact Protection
Body

Weight Line Voltage Electrical Gear IP67 IK08 Natural Anodised Aluminium, Black Anodized Aluminium or Stainless Steel (316) -100 ~ 270V / 50-60Hz IP67 LED Driver (supplied separately)

SPL03.2701.15

Grünzell®

Mounting Accessories

Spike Mount Black Anodized or Natural Anodized Aluminium

